



NOTE:
 MATERIAL:
 1 HOUSING: ENGINEERING PLASTIC, LCP,
 UL 94V-0 RATED, COLOR BLACK.
 2 CONTACT: Ph. BRONZE, PER JIS C5191R-H.
 PLATING:
 1 CONTACT AREA: HARD GOLD PLATING OVER 150"MIN. NICKEL UNDERPLATING.
 2 SOLDERING ZONE: 3.05 μm(120u")MIN. TIN, OR LEAD-FREE PLATING
 PER PART NUMBER DESIGNATION, OVER NICKEL UNDERPLATING.
 3 UNDERPLATING: 1.27 μm(50u") MIN. NICKEL ALLOYER.
 4 PACKAGING: TRAY PACKAGE PER PACKAGING
 5 USING ALL MATERIAL TO ACCORD WITH ROHS CODE.

Scale 1:1
 Recommend PCB Layout

— Tolerances — Unless Otherwise Specified		Title : Express Card 26 Pin Connector	
.0	±0.15	Drawing NO. E-411-126-210	
.00	±0.10	Part NO. E-411-126-210	
.000	±0.05	Unit: mm	
ANGLES ±1°		Scale: 2:1	
Technology CO., LTD.		Size Rev. Sheet	
Approved: Kerwin		A4 01	
Checked: Jim			
Engineer: Angus			
Drawn: Rita			